

5MP Outdoor Full-color Active Deterrence Fixed-focal Wi-Fi Pan & Tilt Network Camera

DH-P5B-PV



Series Overview

The Picoo series of small PT cameras raises the bar on performance. After detecting an intrusion, it triggers sound and light alarms, and then instantly relays vital information on the intrusion to the mobile client, keeping you informed no matter where you are. It supports two-way talk, allowing you to communicate with people in front of the camera in real time. It also can record full-color videos and information of key events using Smart Dual Illuminators, effectively reducing light pollution.



5MP

Clear images with sharp details



Smart Dual Light

Captures color details for post-event



One Camera for 360° View

360° monitoring without blind spots



Sound and Light Alarm

Provides instant alarms to deter



Al Human Detection

Focuses on what matters and reduces false alarms



Al Vehicle Detection

Focuses on what matters and reduces false alarms



Preset Patrol

Guards the places that matter to you regularly



Auto Tracking

Automatic tracking of targets



Abnormal Sound Alarm

Detects abnormal sounds and sends alarms in time



IP65 Protection

Withstands harsh environments



Wi-Fi 6

Seamless integration of speed and anti-interference



Bluetooth Pairing

Fast pairing with Bluetooth



H.265

Advanced H.265 compression technology



SD Card

Low-cost storage



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.









Specifications

Camera

1/3" CMOS Image Sensor

2880 (H) × 1620 (V) Max. Resolution

Electronic Shutter Speed Auto/Manual 1/3 s-1/100,000 s

Up to 30 m (98.43 ft) (IR); Up to 30 m (98.43 ft) (Warm Light) Illumination Distance

Illuminator On/Off Control

Illuminator Number 2 (IR LED); 2 (Warm light)

Pan: 0°-355°; Angle Adjustment Tilt: 0°-65°

Lens

F1.6 Max. Aperture

Field of View H: 78°; V: 40°; D: 93°

Intelligence

Vehicle Detection Yes Human Detection Yes

Video

Video Compression H.265

Main stream: 2880 × 1620@(1-25/30 fps)

sub stream: 640 × 360@(1-25/30 fps) *The values above are the max. frame rates of each

Video Frame Rate stream; for multiple streams, the values will be subjected to the total encoding capacity.

Resolution 5M (2880 × 1620); nHD (640 × 360)

Video Bit Rate H.265: 80 kbps-4096 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR Motion Detection

0°/180° Image Rotation

Audio

Built-in MIC Yes, built-in Mic Built-in Speaker Yes, built-in speaker

G.711a Audio Compression

Network

Network Port RJ-45 (10/100 Base-T)

Wi-Fi IEEE 802.11b/g/n 2.4-2.4835 GHz, 2.4 G

Storage Micro SD card (up to 256 GB)

DMSS Management Software

Mobile Client iOS;Android

Certification

Certifications CE

Power

Power Supply 12 VDC, 1 A

Basic: 1.68 W Max.: 4.56 W (H.265+warm light on) Power Consumption

Environment

Operating Temperature -20 °C to +50 °C (-4 °F to +122 °F)

Operating Humidity ≤95%

Structure

Net Weight

Casing Material Plastic

116 mm × 138 mm × 139 mm (4.57" × 5.43" × 5.47") **Product Dimensions**

 $(L \times W \times H)$ 425 g (0.94 lb)

What's in the box



Smart Illumination













